

Triacs

(0.8 A to 35 A)

General Description

These gated triacs from Teccor Electronics are part of a broad line of bidirectional semiconductors. The devices range in current ratings from 0.8 A to 35 A and in voltages from 200 V to 1000 V.

The triac may be gate triggered from a blocking to conduction state for either polarity of applied voltage and is designed for AC switching and phase control applications such as speed and temperature modulation controls, lighting controls, and static switching relays. The triggering signal is normally applied between the gate and MT1.

Isolated packages are offered with internal construction, having the case or mounting tab electrically isolated from the semiconductor chip. This feature facilitates the use of low-cost assembly and convenient packaging techniques. Tape-and-reel capability is available. See "Packing Options" section of this catalog.

All Teccor triacs have glass-passivated junctions to ensure long-term device reliability and parameter stability. Teccor's glass-passivated junctions offer a rugged, reliable barrier against junction contamination.

Variations of devices covered in this data sheet are available for custom design applications. Consult factory for more information.

Features

- Electrically-isolated packages
- Glass-passivated junctions
- Voltage capability — up to 1000 V
- Surge capability — up to 200 A

Compak Package

- Surface mount package — 0.8 A and 1 A series
- New small profile three-leaded Compak package
- Packaged in embossed carrier tape with 2,500 devices per reel
- Can replace SOT-223

IT(RMS)	Part Number							V _{DRM}	I _{GT}					
	Isolated		Non-isolated						(3) (7) (15)					
(4)	TO-92	TO-220	Compak	TO-202	TO-220	TO-252 D-Pak	TO-251 V-Pak	TO-263 D ² Pak	Volts	mAmps				
MAX	See "Package Dimensions" section for variations. (11)							MIN	MAX			TYP		
0.8 A	Q2X8E3		Q2X3					200	10	10	10		25	
	Q4X8E3		Q4X3					400	10	10	10		25	
	Q6X8E3		Q6X3					600	10	10	10		25	
	Q2X8E4		Q2X4					200	25	25	25		50	
	Q4X8E4		Q4X4					400	25	25	25		50	
	Q6X8E4		Q6X4					600	25	25	25		50	
1 A	Q201E3		Q2N3					200	10	10	10		25	
	Q401E3		Q4N3					400	10	10	10		25	
	Q601E3		Q6N3					600	10	10	10		25	
	Q201E4		Q2N4					200	25	25	25		50	
	Q401E4		Q4N4					400	25	25	25		50	
	Q601E4		Q6N4					600	25	25	25		50	
4 A	Q2004L3		Q2004F31		Q2004D3	Q2004V3		200	10	10	10		25	
	Q4004L3		Q4004F31		Q4004D3	Q4004V3		400	10	10	10		25	
	Q6004L3		Q6004F31		Q6004D3	Q6004V3		600	10	10	10		25	
	Q2004L4		Q2004F41		Q2004D4	Q2004V4		200	25	25	25		50	
	Q4004L4		Q4004F41		Q4004D4	Q4004V4		400	25	25	25		50	
	Q6004L4		Q6004F41		Q6004D4	Q6004V4		600	25	25	25		50	
	Q8004L4				Q8004D4	Q8004V4		800	25	25	25		50	
	QK004L4				QK004D4	QK004V4		1000	25	25	25		50	
6 A	Q2006L4		Q2006F41	Q2006R4			Q2006N4	200	25	25	25		50	
	Q4006L4		Q4006F41	Q4006R4			Q4006N4	400	25	25	25		50	
	Q6006L5		Q6006F51	Q6006R5			Q6006N5	600	50	50	50		75	
	Q8006L5			Q8006R5			Q8006N5	800	50	50	50		75	
	QK006L5			QK006R5			QK006N5	1000	50	50	50		75	
8 A	Q2008L4		Q2008F41	Q2008R4			Q2008N4	200	25	25	25		50	
	Q4008L4		Q4008F41	Q4008R4			Q4008N4	400	25	25	25		50	
	Q6008L5		Q6008F51	Q6008R5			Q6008N5	600	50	50	50		75	
	Q8008L5			Q8008R5			Q8008N5	800	50	50	50		75	
	QK008L5			QK008R5			QK008N5	1000	50	50	50		75	

See "General Notes" on page E2 - 4 and "Electrical Specification Notes" on page E2 - 5.

I_{DRM}		V_{TM}	V_{GT}	I_H	I_{GTM}	P_{GM}	P_{G(AV)}	I_{TSM}	dv/dt(c)	dv/dt		t_{gt}	I²t	di/dt	
(1) (16)		(1) (5)	(2) (6) (15) (18) (19)	(1) (8) (12)	(14)	(14)		(9) (13)	(1) (4) (13)	(1)		(10)			
mAmps		Volts	Volts					Amps		Volts/μSec					
T _C = 25 °C	T _C = 100 °C	T _C = 125 °C	T _C = 25 °C	T _C = 25 °C	mAmps	Amps	Watts	Watts	60/50 Hz	Volts/μSec	T _C = 100 °C	T _C = 125 °C	μSec	Amp ² Sec	Amps/μSec
MAX		MAX	MAX	MAX						TYP	MIN		TYP		
0.02	0.5	1	1.6	2	15	1	10	0.2	10/8.3	1	40	30	2.5	0.41	20
0.02	0.5	1	1.6	2	15	1	10	0.2	10/8.3	1	35	25	2.5	0.41	20
0.02	0.5	1	1.6	2	15	1	10	0.2	10/8.3	1	25	15	2.5	0.41	20
0.02	0.5	1	1.6	2.5	25	1	10	0.2	10/8.3	1	50	40	3	0.41	20
0.02	0.5	1	1.6	2.5	25	1	10	0.2	10/8.3	1	45	35	3	0.41	20
0.02	0.5	1	1.6	2.5	25	1	10	0.2	10/8.3	1	35	25	3	0.41	20
0.02	0.5	1	1.6	2	15	1	10	0.2	20/16.7	1	40	30	2.5	1.6	30
0.02	0.5	1	1.6	2	15	1	10	0.2	20/16.7	1	40	30	2.5	1.6	30
0.02	0.5	1	1.6	2	15	1	10	0.2	20/16.7	1	30	20	2.5	1.6	30
0.02	0.5	1	1.6	2.5	25	1	10	0.2	20/16.7	1	50	40	3	1.6	30
0.02	0.5	1	1.6	2.5	25	1	10	0.2	20/16.7	1	50	40	3	1.6	30
0.02	0.5	1	1.6	2.5	25	1	10	0.2	20/16.7	1	40	30	3	1.6	30
0.05	0.5	2	1.6	2	20	1.2	15	0.3	55/46	2	50	40	2.5	12.5	50
0.05	0.5	2	1.6	2	20	1.2	15	0.3	55/46	2	50	40	2.5	12.5	50
0.05	0.5	2	1.6	2	20	1.2	15	0.3	55/46	2	40	30	2.5	12.5	50
0.05	0.5	2	1.6	2.5	30	1.2	15	0.3	55/46	2	100	75	3	12.5	50
0.05	0.5	2	1.6	2.5	30	1.2	15	0.3	55/46	2	100	75	3	12.5	50
0.05	0.5	2	1.6	2.5	30	1.2	15	0.3	55/46	2	75	50	3	12.5	50
0.05	0.5	2	1.6	2.5	30	1.2	15	0.3	55/46	2	60	40	3	12.5	50
0.05	3		1.6	2.5	30	1.2	15	0.3	55/46	2	50		3	12.5	50
0.05	0.5	2	1.6	2.5	50	1.6	18	0.5	80/65	4	200	120	3	26.5	70
0.05	0.5	2	1.6	2.5	50	1.6	18	0.5	80/65	4	200	120	3	26.5	70
0.05	0.5	2	1.6	2.5	50	1.6	18	0.5	80/65	4	150	100	3	26.5	70
0.05	0.5	2	1.6	2.5	50	1.6	18	0.5	80/65	4	125	85	3	26.5	70
0.05	3		1.6	2.5	50	1.6	18	0.5	80/65	4	100		3	26.5	70
0.05	0.5	2	1.6	2.5	50	1.8	20	0.5	100/83	4	250	150	3	41	70
0.05	0.5	2	1.6	2.5	50	1.8	20	0.5	100/83	4	250	150	3	41	70
0.05	0.5	2	1.6	2.5	50	1.8	20	0.5	100/83	4	220	125	3	41	70
0.05	0.5	2	1.6	2.5	50	1.8	20	0.5	100/83	4	150	100	3	41	70
0.05	3		1.6	2.5	50	1.8	20	0.5	100/83	4	100		3	41	70

See "General Notes" on page E2 - 4 and "Electrical Specification Notes" on page E2 - 5.

$I_{T(RMS)}$	Part Number					V_{DRM}	I_{GT}					I_{DRM}		
	Isolated		Non-isolated				(3) (7) (15)					(1) (16)		
(4) (16)	MT1 MT2 TO-3 Fastpak	MT1 MT2 TO-220	MT2 TO-202	MT2 TO-220	MT2 TO-263 D ² Pak	(1)	(3) (7) (15)					(1) (16)		
MAX	See "Package Dimensions" section for variations. (11)					Volts	mAmps					mAmps		
10 A	Q2010L4		Q2010R4	Q2010N4	200	25	25	25	50		0.05	1		
	Q4010L4		Q4010R4	Q4010N4	400	25	25	25	50		0.05	1		
	Q6010L4		Q6010R4	Q6010N4	600	25	25	25	50		0.05	1		
	Q8010L4		Q8010R4	Q8010N4	800	25	25	25	50		0.1	1		
	QK010L4		QK010R4	QK010N4	1000	25	25	25	50		0.1	3		
	Q2010L5	Q2010F51	Q2010R5	Q2010N5	200	50	50	50		75	0.05	0.5	2	
	Q4010L5	Q4010F51	Q4010R5	Q4010N5	400	50	50	50		75	0.05	0.5	2	
	Q6010L5	Q6010F51	Q6010R5	Q6010N5	600	50	50	50		75	0.05	0.5	2	
	Q8010L5		Q8010R5	Q8010N5	800	50	50	50		75	0.1	0.5	2	
	QK010L5		QK010R5	QK010N5	1000	50	50	50		75	0.1	3		
15 A	Q2015L5		Q2015R5	Q2015N5	200	50	50	50			0.05	0.5	2	
	Q4015L5		Q4015R5	Q4015N5	400	50	50	50			0.05	0.5	2	
	Q6015L5		Q6015R5	Q6015N5	600	50	50	50			0.05	0.5	2	
	Q8015L5		Q8015R5	Q8015N5	800	50	50	50			0.1	1	3	
	QK015L5		QK015R5	QK015N5	1000	50	50	50			0.1	3		
25 A			Q2025R5	Q2025N5	200	50	50	50			0.1	1	3	
			Q4025R5	Q4025N5	400	50	50	50			0.1	1	3	
			Q6025R5	Q6025N5	600	50	50	50			0.1	1	3	
			Q8025R5	Q8025N5	800	50	50	50			0.1	1	3	
			QK025R5	QK025N5	1000	50	50	50			0.1	3		
	Q6025P5				600	50	50	50		120	0.1		5	
35 A	Q8025P5				800	50	50	50		120	0.1		5	
	Q6035P5				600	50	50	50		120	0.1		5	
	Q8035P5				800	50	50	50		120	0.1		5	

Specific Test Conditions

dI/dt — Maximum rate-of-change of on-state current; $I_{GT} = 200$ mA with ≤ 0.1 μ s rise time

dv/dt — Critical rate-of-rise of off-state voltage at rated V_{DRM} gate open

$dv/dt(c)$ — Critical rate-of-rise of commutation voltage at rated V_{DRM} and $I_{T(RMS)}$ commuting $dI/dt = 0.54$ rated $I_{T(RMS)}$ /ms; gate unenergized

I^2t — RMS surge (non-repetitive) on-state current for period of 8.3 ms for fusing

I_{DRM} — Peak off-state current, gate open; V_{DRM} = maximum rated value

I_{GT} — DC gate trigger current in specific operating quadrants;
 $V_D = 12$ V dc

I_{GTM} — Peak gate trigger current

I_H — Holding current (DC); gate open

$I_{T(RMS)}$ — RMS on-state current conduction angle of 360°

I_{TSM} — Peak one-cycle surge

$P_{G(AV)}$ — Average gate power dissipation

P_{GM} — Peak gate power dissipation; $I_{GT} \leq I_{GTM}$

t_{gt} — Gate controlled turn-on time; $I_{GT} = 200$ mA with 0.1 μ s rise time

V_{DRM} — Repetitive peak blocking voltage

V_{GT} — DC gate trigger voltage; $V_D = 12$ V dc; $R_L = 60$ Ω

V_{TM} — Peak on-state voltage at maximum rated RMS current

General Notes

- All measurements are made at 60 Hz with a resistive load at an ambient temperature of +25 °C unless specified otherwise.
- Operating temperature range (T_J) is -65 °C to +125 °C for TO-92, -25 °C to +125 °C for Fastpak, and -40 °C to +125 °C for all other devices.
- Storage temperature range (T_S) is -65 °C to +150 °C for TO-92, -40 °C to +150 °C for TO-202, and -40 °C to +125 °C for all other devices.
- Lead solder temperature is a maximum of 230 °C for 10 seconds, maximum; $\geq 1/16$ " (1.59 mm) from case.
- The case temperature (T_C) is measured as shown on the dimensional outline drawings. See "Package Dimensions" section of this catalog.

V_{TM}	V_{GT}	I_H	I_{GTM}	P_{GM}	P_{G(AV)}	I_{TSM}	dv/dt(c)	dv/dt		t_{gt}	I²t	di/dt
(1) (5)	(2) (6) (15) (18) (19)	(1) (8) (12)	(14)	(14)		(9) (13)	(1) (4) (13)	(1)		(10) (17)		
Volts	Volts					Amps		Volts/ μ Sec				
T _C = 25 °C	T _C = 25 °C	mAmps	Amps	Watts	Watts	60/50 Hz	Volts/ μ Sec	T _C = 100 °C	T _C = 125 °C	μ Sec	Amps ² Sec	Amps/ μ Sec
MAX	MAX	MAX					TYP	MIN		TYP		
1.6	2.5	35	1.8	20	0.5	120/100	2	150		3	60	70
1.6	2.5	35	1.8	20	0.5	120/100	2	150		3	60	70
1.6	2.5	35	1.8	20	0.5	120/100	2	100		3	60	70
1.6	2.5	35	1.8	20	0.5	120/100	2	75		3	60	70
1.6	2.5	35	1.8	20	0.5	120/100	2	50		3	60	70
1.6	2.5	50	1.8	20	0.5	120/100	4	350	225	3	60	70
1.6	2.5	50	1.8	20	0.5	120/100	4	350	225	3	60	70
1.6	2.5	50	1.8	20	0.5	120/100	4	300	200	3	60	70
1.6	2.5	50	1.8	20	0.5	120/100	4	250	175	3	60	70
1.6	2.5	50	1.8	20	0.5	120/100	4	150		3	60	70
1.6	2.5	70	2	20	0.5	200/167	4	400	275	4	166	100
1.6	2.5	70	2	20	0.5	200/167	4	400	275	4	166	100
1.6	2.5	70	2	20	0.5	200/167	4	350	225	4	166	100
1.6	2.5	70	2	20	0.5	200/167	4	300	200	4	166	100
1.6	2.5	70	2	20	0.5	200/167	4	200		4	166	100
1.8	2.5	100	2	20	0.5	200/167	5	400	275	4	166	100
1.8	2.5	100	2	20	0.5	200/167	5	400	275	4	166	100
1.8	2.5	100	2	20	0.5	200/167	5	350	225	4	166	100
1.8	2.5	100	2	20	0.5	200/167	5	300	200	4	166	100
1.8	2.5	100	2	20	0.5	200/167	5	200		4	166	100
1.4	2.75	50	2	20	0.5	250/220	5	550	475	3	260	100
1.4	2.75	50	2	20	0.5	250/220	5	450	400	3	260	100
1.5	2.75	50	2	20	0.5	350/300	5	550	475	3	508	100
1.5	2.75	50	2	20	0.5	350/300	5	450	400	3	508	100

Electrical Specification Notes

- (1) For either polarity of MT2 with reference to MT1 terminal
- (2) For either polarity of gate voltage (V_{GT}) with reference to MT1 terminal
- (3) See Gate Characteristics and Definition of Quadrants.
- (4) See Figure E2.1 through Figure E2.7 for current rating at specific operating temperature.
- (5) See Figure E2.8 through Figure E2.10 for I_T versus V_T.
- (6) See Figure E2.12 for V_{GT} versus T_C.
- (7) See Figure E2.11 for I_{GT} versus T_C.
- (8) See Figure E2.14 for I_H versus T_C.
- (9) See Figure E2.13 for surge rating with specific durations.
- (10) See Figure E2.15 for t_{gt} versus I_{GT}.
- (11) See package outlines for lead form configurations. When ordering special lead forming, add type number as suffix to part number.
- (12) Initial on-state current = 200 mA dc for 0.8 A to 10 A devices, 400 mA dc for 15 A to 35 A devices
- (13) See Figure E2.1 through Figure E2.6 for maximum allowable case temperature at maximum rated current.
- (14) Pulse width ≤ 10 μ s; I_{GT} ≤ I_{GTM}

(15) R_L = 60 Ω for 0.8 A to 10 A triacs; R_L = 30 Ω for 15 A to 35 A triacs

(16) T_C = T_J for test conditions in off state

(17) I_{GT} = 300 mA for 25 A and 35 A devices

(18) Quadrants I, II, III only

(19) Minimum non-trigger V_{GT} at 125 °C is 0.2 V for all except 50 mA MAX QIV devices which are 0.2 V at 110 °C.


Gate Characteristics

Teccor triacs may be turned on between gate and MT1 terminals in the following ways:

- In-phase signals (with standard AC line) using Quadrants I and III
- Application of unipolar pulses (gate always positive or negative), using Quadrants II and III with negative gate pulses and Quadrants I and IV with positive gate pulses

However, due to higher gate requirements for Quadrant IV, it is recommended that only negative pulses be applied. If positive pulses are required, see "Sensitive Triacs" section of this catalog or contact the factory. Also, see Figure AN1002.8, "Amplified Gate" Thyristor Circuit.

In all cases, if maximum surge capability is required, pulses should be a minimum of one magnitude above I_{GT} rating with a steep rising waveform ($\leq 1 \mu\text{s}$ rise time).



Definition of Quadrants

Electrical Isolation

Teccor's isolated triac packages will withstand a minimum high potential test of 2500 V ac rms from leads to mounting tab or base, over the operating temperature range of the device. The following isolation table shows standard and optional isolation ratings.

Electrical Isolation from Leads to Mounting Tab *		
V AC RMS	TO-220 Isolated	Fastpak Isolated
2500	Standard	Standard
4000	Optional **	N/A

* UL Recognized File E71639

** For 4000 V isolation, use V suffix in part number.

Thermal Resistance (Steady State) $R_{\theta JC} [R_{\theta JA}] (\text{TYP.}) ^\circ\text{C/W}$										
Package Code	P	E	C	F	F2	L	R	D	V	N
Type										
0.8 A		60 [135]	60 *							
1 A		50 [95]	40 *							
4 A				3.5 [45]	6 [70]	3.6 [50]		3.5	6.0 [70]	
6 A				3.8		3.3	1.8 [45]			1.8
8 A				3.3		2.8	1.5			1.5
10 A				3.5		2.6	1.3			1.3
15 A						2.1	1.1			1.1
25 A	1.6						0.89			0.89
35 A	1.5									

* Mounted on 1 cm² copper foil surface; two-ounce copper foil




Figure E2.1 Maximum Allowable Case Temperature versus On-state Current (0.8 A and 1 A)




Figure E2.4 Maximum Allowable Case Temperature versus On-state Current (10 A)




Figure E2.2 Maximum Allowable Case Temperature versus On-state Current (4 A and 6 A)




Figure E2.5 Maximum Allowable Case Temperature versus On-state Current (15 A)




Figure E2.3 Maximum Allowable Case Temperature versus On-state Current (8 A and 10 A)




Figure E2.6 Maximum Allowable Case Temperature versus On-state Current (25 A and 35 A)




Figure E2.7 Maximum Allowable Ambient Temperature versus On-state Current




Figure E2.8 On-state Current versus On-state Voltage (Typical) (0.8 A and 1 A)




Figure E2.9 On-state Current versus On-state Voltage (Typical) (4 A, 6 A, 8 A, and 10 A)




Figure E2.10 On-state Current versus On-state Voltage (Typical) (15 A and 25 A)




Figure E2.11 Normalized DC Gate Trigger Current for All Quadrants versus Case Temperature




Figure E2.12 Normalized DC Gate Trigger Voltage for All Quadrants versus Case Temperature




Figure E2.13 Peak Surge Current versus Surge Current Duration




Figure E2.14 Normalized DC Holding Current versus Case Temperature




Figure E2.15 Turn-on Time versus Gate Trigger Current (Typical)




Figure E2.16 Power Dissipation (Typical) versus On-state Current (0.8 A and 1 A)




Figure E2.19 Power Dissipation (Typical) versus RMS On-state Current (4 A)




Figure E2.17 Power Dissipation (Typical) versus On-state Current (6 A to 10 A and 15 A)




Figure E2.18 Power Dissipation (Typical) versus On-state Current (25 A to 35 A)