MOTOROLA

MC1723C

Voltage Regulator

The MC1723C is a positive or negative voltage regulator designed to deliver load current to 150 mAdc. Output current capability can be increased to several amperes through use of one or more external pass transistors. MC1723C is specified for operation over the commercial temperature range (0° to +70°C).

- Output Voltage Adjustable from 2.0 Vdc to 37 Vdc
- Output Current to 150 mAdc Without External Pass Transistors
- 0.01% Line and 0.03% Load Regulation
- Adjustable Short Circuit Protection

VOLTAGE REGULATOR

SEMICONDUCTOR TECHNICAL DATA



P SUFFIX
PLASTIC PACKAGE
CASE 646



D SUFFIX
PLASTIC PACKAGE
CASE 751A
(SO–14)

Figure 1. Representative Schematic Diagram



Figure 2. Typical Circuit Connection



$$V_O \cong 7\left(\frac{R1 + R2}{R2}\right) \quad I_{SC} = \frac{V_{sense}}{R_{SC}} = \frac{0.66}{R_{SC}} \text{ at } T_J = +25°C$$

For best results 10 k < R2 < 100 k
For minimum drift R3 = R1 | | R2

Figure 3. Typical NPN Current Boost Connection



ORDERING INFORMATION

Device	Alternate	Operating Temperature Range	Package
MC1723CD	–	T_A = 0° to +70°C	SO–14
MC1723CP	LM723CN µA723PC		Plastic DIP

© Motorola, Inc. 1996

This datasheet has been downloaded from http://www.digchip.com at this page

MAXIMUM RATINGS (T_A = +25°C, unless otherwise noted.)

Rating	Symbol	Value	Unit
Pulse Voltage from V_{CC} to V_{EE} (50 ms)	$V_{I(p)}$	50	V_{pk}
Continuous Voltage from V_{CC} to V_{EE}	V_I	40	Vdc
Input–Output Voltage Differential	V_I–V_O	40	Vdc
Maximum Output Current	I_L	150	mAdc
Current from V_{ref}	I_{ref}	15	mAdc
Current from V_Z	I_Z	25	mA
Voltage Between Noninverting Input and V_{EE}	V_{ie}	8.0	Vdc
Differential Input Voltage	V_{id}	±5.0	Vdc
Power Dissipation and Thermal Characteristics T_A = +25°C Derate above T_A = +25°C Thermal Resistance, Junction–to–Air	 P_D $1/\theta_{JA}$ θ_{JA}	 1.25 10 100	 W mW/°C °C/W
Operating and Storage Junction Temperature Range	T_J, T_{stg}	–65 to +175	°C
Operating Ambient Temperature Range	T_A	0 to +70	°C

ELECTRICAL CHARACTERISTICS (T_A = +25°C, V_{in} 12 Vdc, V_O = 5.0 Vdc, I_L = 1.0 mAdc, R_{SC} = 0, C1 = 100 pF, C_{ref} = 0 and divider impedance as seen by the error amplifier ≤ 10 kΩ connected as shown in Figure 2, unless otherwise noted.)

Characteristics	Symbol	Min	Typ	Max	Unit
Input Voltage Range	V_I	9.5	–	40	Vdc
Output Voltage Range	V_O	2.0	–	37	Vdc
Input–Output Voltage Differential	V_I–V_O	3.0	–	38	Vdc
Reference Voltage	V_{ref}	6.80	7.15	7.50	Vdc
Standby Current Drain (I_L = 0, V_{in} = 30 V)	I_{IB}	–	2.3	4.0	mAdc
Output Noise Voltage (f = 100 Hz to 10 kHz) C_{ref} = 0 C_{ref} = 5.0 μF	V_n	 – –	 20 2.5	 – –	μV(RMS)
Average Temperature Coefficient of Output Voltage (T_{low} < T_A < T_{high})	TCV_O	–	0.003	0.015	%/°C
Line Regulation (T_A = 25°C) { 12 V < V_{in} < 15 V 12 V < V_{in} < 40 V (T_{low} < T_A < T_{high}) 12 V < V_{in} < 15 V	Reg_{line}	 – – –	 0.01 0.1 –	 0.1 0.5 0.3	% V_O
Load Regulation (1.0 mA < I_L < 50 mA) T_A = 25°C T_{low} < T_A < T_{high}	Reg_{load}	 – –	 0.03 –	 0.2 0.6	% V_O
Ripple Rejection (f = 50 Hz to 10 kHz) C_{ref} = 0 C_{ref} = 5.0 μF	RR	 – –	 74 86	 – –	dB
Short Circuit Current Limit (R_{SC} = 10 Ω, V_O = 0)	I_{SC}	–	65	–	mAdc
Long Term Stability	$\Delta V_O/\Delta t$	–	0.1	–	%/1000 Hr.

NOTE: T_{low} to T_{high} = 0° to +70°C

Figure 4. Maximum Load Current as a Function of Input–Output Voltage Differential



Figure 5. Load Regulation Characteristics Without Current Limiting



Figure 6. Load Regulation Characteristics With Current Limiting



Figure 7. Load Regulation Characteristics With Current Limiting



Figure 8. Current Limiting Characteristics



Figure 9. Current Limiting Characteristics as a Function of Junction Temperature



Figure 10. Line Regulation as a Function of Input–Output Voltage Differential



Figure 11. Load Regulation as a Function of Input–Output Voltage Differential



Figure 12. Standby Current Drain as a Function of Input Voltage



Figure 13. Line Transient Response



Figure 14. Load Transient Response



Figure 15. Output Impedance as Function of Frequency



Figure 16. Typical Connection for 2 < V_O < 7



$V_O \cong 7\left[\frac{R2}{R1+R2}\right]$ $I_{SC} = \frac{V_{sense}}{R_{SC}} \cong \frac{0.66}{RSC}$ at T_J = + 25°C

For best results 10 k < R1 +R2 < 100 k
For minimum drift R3 = R1 R2

Figure 17. Foldback Connection



$R_A = \frac{a}{1-a}\ 10\ k\Omega$ where $a = \frac{V_{sense}}{V_O}\left[\frac{I_{knee}}{I_{SC}} - 1\right]$

$R_{SC} = \frac{V_{sense}}{(1-a)\ I_{SC}}$

Figure 18. +5.0 V, 1.0 A Switching Regulator



Figure 19. +5.0 V, 1.0 A High Efficiency Regulator



Figure 20. +15 V, 1.0 A Regulator with Remote Sense



Figure 21. –15 V Negative Regulator



Figure 22. +12V, 1.0 A Regulator
(Using PNP Current Boost)



OUTLINE DIMENSIONS

P SUFFIX
PLASTIC PACKAGE
CASE 646–06
ISSUE L



NOTES:
1. LEADS WITHIN 0.13 (0.005) RADIUS OF TRUE POSITION AT SEATING PLANE AT MAXIMUM MATERIAL CONDITION.
2. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
3. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
4. ROUNDED CORNERS OPTIONAL.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.715	0.770	18.16	19.56
B	0.240	0.260	6.10	6.60
C	0.145	0.185	3.69	4.69
D	0.015	0.021	0.38	0.53
F	0.040	0.070	1.02	1.78
G	0.100 BSC		2.54 BSC	
H	0.052	0.095	1.32	2.41
J	0.008	0.015	0.20	0.38
K	0.115	0.135	2.92	3.43
L	0.300 BSC		7.62 BSC	
M	0°	10°	0°	10°
N	0.015	0.039	0.39	1.01

D SUFFIX
PLASTIC PACKAGE
CASE 751A–03
(SO–14)
ISSUE F



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	8.55	8.75	0.337	0.344
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27 BSC		0.050 BSC	
J	0.19	0.25	0.008	0.009
K	0.10	0.25	0.004	0.009
M	0°	7°	0°	7°
P	5.80	6.20	0.228	0.244
R	0.25	0.50	0.010	0.019

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. “Typical” parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and Ⓜ are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:
USA / EUROPE / Locations Not Listed: Motorola Literature Distribution; P.O. Box 20912; Phoenix, Arizona 85036. 1–800–441–2447 or 602–303–5454

MFAX: RMFAX0@email.sps.mot.com – TOUCHTONE 602–244–6609
INTERNET: http://Design–NET.com

JAPAN: Nippon Motorola Ltd.; Tatsumi–SPD–JLDC, 6F Seibu–Butsuryu–Center, 3–14–2 Tatsumi Koto–Ku, Tokyo 135, Japan. 03–81–3521–8315

ASIA / PACIFIC: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park, 51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852–26629298