

2N4870
2N4871

**SILICON
PN UNIJUNCTION TRANSISTORS**



www.centrasemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR 2N4870 and 2N4871 are silicon PN unijunction transistors designed for oscillator, triggering and timing applications.



TO-92 CASE

MARKING: FULL PART NUMBER

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$)

Emitter Reverse Voltage	
Interbase Voltage	
RMS Emitter Current	
Peak Emitter Current (Duty Cycle $\leq 1\%$, PRR=10pps)	
RMS Power Dissipation	
Operating Junction Temperature	
Storage Temperature	

SYMBOL

V_{B2E}	30
V_{B2B1}	35
I_e	1.5
i_e	1.0
P_D	300
T_J	-65 to +125
T_{stg}	-65 to +150

UNITS

V
V
A
A
mW
$^\circ\text{C}$
$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS: ($T_A=25^\circ\text{C}$)

SYMBOL	TEST CONDITIONS
η	$V_{B2B1}=10\text{V}$
R_{BB}	$V_{B2B1}=3.0\text{V}$
I_{EB20}	$V_{B2E}=30\text{V}$
I_V	$V_{B2B1}=20\text{V}$, $R_{B2}=100\Omega$
I_P	$V_{B2B1}=25\text{V}$
V_{OB1}	$V_1=20\text{V}$


	2N4870		2N4871		UNITS
	MIN	MAX	MIN	MAX	
η	0.56	0.75	0.70	0.85	
R_{BB}	4.0	9.1	4.0	9.1	k Ω
I_{EB20}	-	1.0	-	1.0	μA
I_V	2.0	-	4.0	-	mA
I_P	-	5.0	-	5.0	μA
V_{OB1}	3.0	-	5.0	-	V

2N4870
2N4871

SILICON
PN UNIJUNCTION TRANSISTORS



TO-92 CASE - MECHANICAL OUTLINE



SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A (DIA)	0.175	0.205	4.45	5.21
B	0.170	0.210	4.32	5.33
C	0.500	-	12.70	-
D	0.016	0.022	0.41	0.56
E	0.100		2.54	
F	0.050		1.27	
G	0.125	0.165	3.18	4.19
H	0.080	0.105	2.03	2.67
I	0.015		0.38	

TO-92 (REV: R1)

LEAD CODE:

- 1) Base 1
- 2) Emitter
- 3) Base 2

MARKING:
FULL PART NUMBER

R1

R1 (23-April 2013)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Central Semiconductor:](#)

[2N4870](#) [2N4871](#)