Silicon Switching Diodes

- Switching applications
- High breakdown voltage
- Pb-free (RoHS compliant) package[1)]
- Qualified according AEC Q101



BAW78D **BAW79D**





Type	Package	Configuration	Marking
BAW78D	SOT89	single	GD
BAW79D	SOT89	common cathode	GH

Maximum Ratings at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Value	Unit
Diode reverse voltage	V_R	400	V
Peak reverse voltage	V_{RM}	400	
Forward current	I_F	1	A
Peak forward current	I_{FM}	1	
Peak forward current	I_{FM}	1	
Surge forward current, t = 1 µs	I_{FS}	10	
Non-repetitive peak surge forward current	I_{FSM}	-	
Total power dissipation BAW78D, $T_S \leq$ 125°C BAW79D, $T_S \leq$ 115°C	P_{tot}	 1 1	W
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-65 ... 150	

[1]Pb-containing package may be available upon special request

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point[1)]	R_{thJS}		K/W
BAW78D		≤ 25	
BAW79D		≤ 35	

Electrical Characteristics at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Breakdown voltage $I_{(BR)}$ = 100 µA	$V_{(BR)}$	400	-	-	V
Reverse current	I_R	-	-		µA
V_R = 400 V		-	-	1	
V_R = 400 V, T_A = 150 °C				50	
Forward voltage	V_F				V
I_F = 1 A		-	-	1.6	
I_F = 2 A		-	-	2	
AC Characteristics					
Diode capacitance V_R = 0 V, f = 1 MHz	C_T	-	10	-	pF
Reverse recovery time I_F = 200mA, I_R = 200mA, measured at I_R = 20mA R_L = 100Ω	t_{rr}	-	1 ,	-	µs

Test circuit for reverse recovery time



Puls generator: t_p = 10µs, D = 0.05,
t_r = 0.6ns, R_i = 50Ω

Oscillograp: R = 50Ω, t_r = 0.35ns
C ≤ 1pF

[1]For calculation of R_{thJA} please refer to Application Note Thermal Resistance

Reverse current $I_R = f(T_A)$

V_R = 400V



Forward current $I_F = f(V_F)$

T_A = 25°C



Peak forward current $I_{FM} = f(t_p)$



Forward current $I_F = f(T_S)$

BAW78D



Forward current $I_F = f(T_S)$

BAW79D



Package Outline



1) Ejector pin markings possible

Foot Print



Marking Layout (Example)



Standard Packing

Reel ø180 mm = 1.000 Pieces/Reel
Reel ø330 mm = 4.000 Pieces/Reel



Edition 2006-02-01
Published by
Infineon Technologies AG
81726 München, Germany
© Infineon Technologies AG 2007.
All Rights Reserved.

Attention please!

The information given in this dokument shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.
Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system.
Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.